TAVAKOL ELECTRONIC
توکل الکترونیک
مرجع تخصصی تأمین قطعات الکترونیکی اورجینال

این دیتاشیت توسط توکل الکترونیک تهیه و ارائه شده است.
جهت مشاهده قیمت، موجودی و ثبت سفارش این قطعه به وب‌سایت توکل الکترونیک مراجعه فرمایید.

مشاهده قیمت و خرید
برای خرید و مشاهده سایر محصولات کلیک کنید

isc®

INCHANGE SEMICONDUCTOR

isc N-Channel MOSFET Transistor — 2SK1096

FEATURES

- Drain Current -I_D= 13A@ T_C=25℃
- Drain Source Voltage -V_{DSS}= 60V(Min)
- Static Drain-Source On-Resistance
  -$R_{DS(on)}$ =0.12Ω(Max)@V_{GS}= 10V



Pin 1.Gate
2.Drain
3.Source

TO-220F package

DESCRIPTION

- Motor drive, DC-DC converter, power switch and solenoid drive.

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage	60	V
V_{GS}	Gate-Source Voltage-Continuous	±20	V
I_D	Drain Current-Continuous	13	A
I_{DM}	Drain Current-Single Pulse	52	A
P_D	Total Dissipation @T_C=25℃	30	W
T_J	Max. Operating Junction Temperature	150	℃
T_{stg}	Storage Temperature	-55~150	℃

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j\text{-}c}$	Thermal Resistance, Junction to Case	4.17	℃/W



DIM	mm		
	MIN	TYP.	MAX
A	14.95	15.00	15.05
B	10.00	10.05	10.10
C	4.40	4.50	4.60
D	0.75	0.83	0.90
F	3.10	3.20	3.30
H	3.70	3.80	3.90
J	0.50	0.60	0.70
K	13.40	13.50	13.60
L	1.10	1.20	1.30
N	5.00	5.10	5.20
Q	2.70	2.80	2.90
R	2.20	2.30	2.40
S	2.65	2.78	2.90
U	6.40	6.50	6.60

Download from alldatasheet.com

isc N-Channel MOSFET Transistor 2SK1096

ELECTRICAL CHARACTERISTICS（T_C=25℃ unless otherwise specified）

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}= 0; I_D= 1.0mA	60	--	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}= 60V; V_{GS}= 0 V	--	500	uA
I_{GSS}	Gate-Body Leakage Current	V_{GS}= ±20V;V_{DS}= 0 V	--	±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}= V_{GS}; I_D= 1.0mA	1.0	2.5	V
$R_{DS(on)}$	Drain-Source On-Resistance	V_{GS}= 10V; I_D=7.0A	--	0.12	Ω
V_{SD}	Forward On-Voltage	I_S= 7.0A; V_{GS}= 0 V	--	1.74	V

PRODUCT DISCLAIMER

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

It is strictly prohibited to reprint or copy part or all of this datasheet without permission from ISC.

Download from alldatasheet.com