TAVAKOL ELECTRONIC
توکل الکترونیک
مرجع تخصصی تأمین قطعات الکترونیکی اورجینال
این دیتاشیت توسط توکل الکترونیک تهیه و ارائه شده است.
جهت مشاهده قیمت، موجودی و ثبت سفارش این قطعه به وب‌سایت توکل الکترونیک مراجعه فرمایید.
مشاهده قیمت و خرید
برای خرید و مشاهده سایر محصولات کلیک کنید

isc®

INCHANGE SEMICONDUCTOR

isc N-Channel MOSFET Transistor 2SK538



DESCRIPTION

- Drain Current –I_D=3A@ T_C=25℃
- Drain Source Voltage-
  : V_{DSS}=900V(Min)
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed especially for high voltage,high speed applications, such as off-line switching power supplies , UPS,AC and DC motor controls,relay and solenoid drivers.



DIM	mm MIN	MAX
A	19.60	20.10
B	15.30	15.70
C	4.00	4.60
D	0.90	1.10
F	3.20	3.40
H	2.90	3.10
J	0.50	0.70
K	19.90	21.30
L	1.20	2.20
N	10.80	11.00
Q	4.40	4.60
R	3.30	3.35
S	1.40	1.60
T	1.00	1.20
U	2.10	2.30
Z	7.90	9.10

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	ARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage (V_{GS}=0)	900	V
V_{GS}	Gate-Source Voltage	±20	V
I_D	Drain Current-continuous@ TC=25℃	3	A
P_{tot}	Total Dissipation@TC=25℃	100	W
T_j	Max. Operating Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-55~150	℃

isc N-Channel MOSFET Transistor 2SK538

• **ELECTRICAL CHARACTERISTICS (T_C=25℃)**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0; I_D= 10mA	900			V
$V_{GS(TH)}$	Gate Threshold Voltage	V_{DS}= 10V; I_D= 1mA	1.5		3.5	V
$R_{DS(ON)}$	Drain-Source On-stage Resistance	V_{GS}= 10V; I_D=1.5A			4.5	Ω
I_{GSS}	Gate Source Leakage Current	V_{GS}= ±20V; V_{DS}= 0			±100	nA
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=900V; V_{GS}= 0			300	uA

NOTICE：
ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.
ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.
ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.