TAVAKOL ELECTRONIC
توکل الکترونیک
مرجع تخصصی تأمین قطعات الکترونیکی اورجینال
این دیتاشیت توسط توکل الکترونیک تهیه و ارائه شده است.
جهت مشاهده قیمت، موجودی و ثبت سفارش این قطعه به وب‌سایت توکل الکترونیک مراجعه فرمایید.
مشاهده قیمت و خرید
برای خرید و مشاهده سایر محصولات کلیک کنید

N-CHANNEL MOS FIELD EFFECT POWER TRANSISTOR

2SK785

DESCRIPTION The 2SK785 is N-channel MOS Field Effect Power Transistor designed for switching power supplies DC-DC converters.

FEATURES

- Suitable for switching power supplies, actuater controls, and pulse circuits.
- Low $R_{DS(on)}$
- No second breakdown

PACKAGE DIMENSIONS
in millimeters (inches)



ABSOLUTE MAXIMUM RATINGS

Maximum Temperatures
- Storage Temperature . . . . . −55 to +150 °C
- Channel Temperature . . . . . 150 °C Maximum

Maximum Power Dissipation (T_c = 25 °C)
- Total Power Dissipation . . . . . 150 W

Maximum Voltages and Currents (T_a = 25 °C)
- V_{DSS} Drain to Source Voltage . . . . . 500 V
- V_{GSS} Gate to Source Voltage. . . . . ±20 V
- $I_{D(DC)}$ Drain Current (DC) . . . . . ±20 A
- $I_{D(pulse)}$ Drain Current (pulse)* . . . . . ±80 A

* PW ≤ 300 μs, Duty Cycle ≤ 2 %

ELECTRICAL CHARACTERISTICS (T_a = 25 °C)

SYMBOL	CHARACTERISTIC	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
I_{DSS}	Drain Leakage Current			100	μA	V_{DS} = 500 V, V_{GS} = 0
I_{GSS}	Gate to Source Leakage Current			±100	nA	V_{GS} = ±20 V, V_{DS} = 0
$V_{GS(off)}$	Gate to Source Cutoff Voltage	1.5		3.5	V	V_{DS} = 10 V, I_D = 1 mA
$\|y_{fs}\|$	Forward Transfer Admittance	9.0			S	V_{DS} = 10 V, I_D = 10 A
$R_{DS(on)}$	Drain to Source On-State Resistance		0.3	0.4	Ω	V_{GS} = 10 V, I_D = 10 A
C_{iss}	Input Capacitance		3000		pF	V_{DS} = 10 V, V_{GS} = 0, f = 1 MHz
C_{oss}	Output Capacitance		900		pF	
C_{rss}	Reverse Transfer Capacitance		350		pF	
$t_{d(on)}$	Turn-On Delay Time		45		ns	I_D = 10 A, V_{CC} ≒ 150 V, $V_{GS(on)}$ = 10 V, R_L = 15 Ω, R_{in} = 10 Ω
t_r	Rise Time		60		ns	
$t_{d(off)}$	Turn-Off Delay Time		100		ns	
t_f	Fall Time		80		ns	

NEC cannot assume any responsibility for any circuits shown or represent that they are free from patent infringement

© NEC Corporation 1987

TYPICAL CHARACTERISTICS (T_a = 25 °C)

DERATING FACTOR OF FORWARD BIAS SAFE OPERATING AREA



TOTAL POWER DISSIPATION vs. CASE TEMPERATURE



FORWARD BIAS SAFE OPERATING AREA



DRAIN CURRENT vs. DRAIN TO SOURCE VOLTAGE



FORWARD TRANSFER ADMITTANCE vs. DRAIN CURRENT



SOURCE TO DRAIN DIODE FORWARD VOLTAGE



CAPACITANCE vs. DRAIN TO SOURCE VOLTAGE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. GATE TO SOURCE VOLTAGE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. CHANNEL TEMPERATURE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. DRAIN CURRENT



TRANSFER CHARACTERISTIC



GATE TO SOURCE CUTOFF VOLTAGE vs. CHANNEL TEMPERATURE



SWITCHING CHARACTERISTICS



NORMALIZED TRANSIENT IMPEDANCE vs. PULSE WIDTH



SWITCHING TIME TEST CIRCUIT