TAVAKOL ELECTRONIC
توکل الکترونیک
مرجع تخصصی تأمین قطعات الکترونیکی اورجینال
این دیتاشیت توسط توکل الکترونیک تهیه و ارائه شده است.
جهت مشاهده قیمت، موجودی و ثبت سفارش این قطعه به وب‌سایت توکل الکترونیک مراجعه فرمایید.
مشاهده قیمت و خرید
برای خرید و مشاهده سایر محصولات کلیک کنید

isc®

INCHANGE SEMICONDUCTOR

# isc N-Channel MOSFET Transistor IPP032N06N3，IIPP032N06N3




## • FEATURES

- Static drain-source on-resistance:
  $R_{DS}(on)$ ≤2.9mΩ
- Enhancement mode
- Fast Switching Speed
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

## • DESCRIPTION

- reliable device for use in a wide variety of applications

## • ABSOLUTE MAXIMUM RATINGS($T_a$=25℃)

| SYMBOL | PARAMETER | VALUE | UNIT |
|---|---|---|---|
| $V_{DSS}$ | Drain-Source Voltage | 60 | V |
| $V_{GS}$ | Gate-Source Voltage | ±20 | V |
| $I_D$ | Drain Current-Continuous | 120 | A |
| $I_{DM}$ | Drain Current-Single Pulsed | 480 | A |
| $P_D$ | Total Dissipation @$T_C$=25℃ | 188 | W |
| $T_j$ | Max. Operating Junction Temperature | 175 | ℃ |
| $T_{stg}$ | Storage Temperature | -55~175 | ℃ |

## • THERMAL CHARACTERISTICS

| SYMBOL | PARAMETER | MAX | UNIT |
|---|---|---|---|
| Rth(ch-c) | Channel-to-case thermal resistance | 0.8 | ℃/W |
| Rth(ch-a) | Channel-to-ambient thermal resistance | 62 | ℃/W |




| DIM | mm MIN | mm MAX |
|---|---|---|
| A | 15.50 | 15.90 |
| B | 9.90 | 10.20 |
| C | 4.20 | 4.50 |
| D | 0.70 | 0.90 |
| F | 3.40 | 3.70 |
| G | 4.98 | 5.18 |
| H | 2.68 | 2.90 |
| J | 0.44 | 0.60 |
| K | 13.00 | 13.40 |
| L | 1.10 | 1.45 |
| Q | 2.70 | 2.90 |
| R | 2.30 | 2.70 |
| S | 1.29 | 1.35 |
| U | 6.45 | 6.65 |
| V | 8.66 | 8.86 |

# isc N-Channel MOSFET Transistor IPP032N06N3，IIPP032N06N3

## ELECTRICAL CHARACTERISTICS

**$T_C$=25℃ unless otherwise specified**

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP | MAX | UNIT |
|---|---|---|---|---|---|---|
| $BV_{DSS}$ | Drain-Source Breakdown Voltage | $V_{GS}$=0V; $I_D$ = 1mA | 60 | | | V |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{DS}$=$V_{GS}$; $I_D$=118 μA | 2 | | 4 | V |
| $R_{DS(on)}$ | Drain-Source On-Resistance | $V_{GS}$=10V; $I_D$=100A | | | 3.2 | mΩ |
| $I_{GSS}$ | Gate-Source Leakage Current | $V_{GS}$=20V;$V_{DS}$=0V | | | 0.1 | μA |
| $I_{DSS}$ | Drain-Source Leakage Current | $V_{DS}$=60V; $V_{GS}$= 0V | | | 2 | μA |
| $V_{SD}$ | Diode forward voltage | $I_F$ =100A, $V_{GS}$ = 0 V | | | 1.2 | V |

**NOTICE：**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.