TAVAKOL ELECTRONIC
توکل الکترونیک
مرجع تخصصی تأمین قطعات الکترونیکی اورجینال
این دیتاشیت توسط توکل الکترونیک تهیه و ارائه شده است.
جهت مشاهده قیمت، موجودی و ثبت سفارش این قطعه به وب‌سایت توکل الکترونیک مراجعه فرمایید.
مشاهده قیمت و خرید
برای خرید و مشاهده سایر محصولات کلیک کنید

FAIRCHILD SEMICONDUCTOR TM

IRFR320, IRFU320

Data Sheet | July 1999 | File Number 2412.3

3.1A, 400V, 1.800 Ohm, N-Channel Power MOSFETs

These are N-Channel enhancement mode silicon gate power field effect transistors. They are advanced power MOSFETs designed, tested, and guaranteed to withstand a specified level of energy in the breakdown avalanche mode of operation. All of these power MOSFETs are designed for applications such as switching regulators, switching convertors, motor drivers, relay drivers, and drivers for high power bipolar switching transistors requiring high speed and low gate drive power. These types can be operated directly from integrated circuits.

Formerly developmental type TA17404.

Ordering Information

PART NUMBER	PACKAGE	BRAND
IRFR320	TO-252AA	IFR320
IRFU320	TO-251AA	IFU320

NOTE: When ordering, use the entire part number. Add the suffix 9A to obtain the TO-252AA variant in tape and reel, i.e., IRFR3209A.

Features

- 3.1A, 400V
- $r_{DS(ON)} = 1.800\Omega$
- Single Pulse Avalanche Energy Rated
- SOA is Power Dissipation Limited
- Nanosecond Switching Speeds
- Linear Transfer Characteristics
- High Input Impedance
- Related Literature
  - TB334 “Guidelines for Soldering Surface Mount Components to PC Boards”

Symbol



Packaging

JEDEC TO-251AA



JEDEC TO-252AA



©2001 Fairchild Semiconductor Corporation

Absolute Maximum Ratings $T_C = 25^oC$, Unless Otherwise Specified

		IRFR320, IRFU320	UNITS
Drain to Source Voltage (Note 1)	V_{DS}	400	V
Drain to Gate Voltage (R_{GS} = 20kΩ) (Note 1)	V_{DGR}	400	V
Continuous Drain Current	I_D	3.1	A
$T_C = 100^oC$	I_D	2.0	A
Pulsed Drain Current (Note 3)	I_{DM}	12	A
Gate to Source Voltage	V_{GS}	±20	V
Maximum Power Dissipation	P_D	50	W
Linear Derating Factor		0.4	$W/^oC$
Single Pulse Avalanche Energy Rating (Note 4)	E_{AS}	190	mJ
Operating and Storage Temperature	T_J, T_{STG}	-55 to 150	^oC
Maximum Temperature for Soldering			
Leads at 0.063in (1.6mm) from Case for 10s	T_L	300	^oC
Package Body for 10s, See Techbrief 334	T_{pkg}	260	^oC

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

NOTE:

1. $T_J = 25^oC$ to 125^oC.

Electrical Specifications $T_C = 25^oC$, Unless Otherwise Specified

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNITS
Drain to Source Breakdown Voltage	BV_{DSS}	I_D = 250μA, V_{GS} = 0V, (Figure 10)		400	-	-	V
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{GS} = V_{DS}$, I_D = 250μA		2.0	-	4.0	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = Rated BV_{DSS}, V_{GS} = 0V		-	-	25	μA
		V_{DS} = 0.8 x Rated BV_{DSS}, V_{GS} = 0V, $T_J = 125^oC$		-	-	250	μA
On-State Drain Current (Note 2)	$I_{D(ON)}$	$V_{DS} > I_{D(ON)} \times r_{DS(ON)MAX}$, V_{GS} = 10V, (Figure 7)		3.1	-	-	A
Gate to Source Leakage Current	I_{GSS}	V_{GS} = ±20V		-	-	±100	nA
Drain to Source On Resistance (Note 2)	$r_{DS(ON)}$	I_D = 1.7A, V_{GS} = 10V, (Figures 8, 9)		-	1.600	1.800	Ω
Forward Transconductance (Note 2)	g_{fs}	$V_{DS} \geq 10V$, I_D = 2.0A, (Figure 12)		1.7	2.6	-	S
Turn-On Delay Time	$t_{d(ON)}$	V_{DD} = 200V, $I_D \approx$ 3.1A, R_{GS} = 18Ω, R_L = 63Ω, V_{GS} = 10V MOSFET Switching Times are Essentially Independent of Operating Temperature		-	10	15	ns
Rise Time	t_r			-	14	21	ns
Turn-Off Delay Time	$t_{d(OFF)}$			-	30	45	ns
Fall Time	t_f			-	13	20	ns
Total Gate Charge (Gate to Source + Gate to Drain)	$Q_{g(TOT)}$	V_{GS} = 10V, I_D = 3.1A, V_{DS} = 0.8 x Rated BV_{DSS}, $I_{G(REF)}$ = 1.5mA, (Figure 14) Gate Charge is Essentially Independent of Operating Temperature		-	13	20	nC
Gate to Source Charge	Q_{gs}			-	2.2	3.3	nC
Gate to Drain "Miller" Charge	Q_{gd}			-	7.2	11	nC
Input Capacitance	C_{ISS}	V_{DS} = 25V, V_{GS} = 0V, f = 1MHz, (Figure 11)		-	350	-	pF
Output Capacitance	C_{OSS}			-	64	-	pF
Reverse Transfer Capacitance	C_{RSS}			-	8.1	-	pF
Internal Drain Inductance	L_D	Measured From the Drain Lead, 6.0mm (0.25in) from Package to Center of Die	Modified MOSFET Symbol Showing the Internal Device Inductances	-	4.5	-	nH
Internal Source Inductance	L_S	Measured From the Source Lead, 6.0mm (0.25in) from Package to Source Bonding Pad		-	7.5	-	nH
Thermal Resistance, Junction to Case	$R_{\theta JC}$			-	-	2.5	$^oC/W$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	Typical Solder Mount		-	-	110	$^oC/W$

©2001 Fairchild Semiconductor Corporation

Source to Drain Diode Specifications

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Continuous Source to Drain Current	I_{SD}	Modified MOSFET Symbol Showing the Integral Reverse P-N Junction Rectifier 	-	-	3.1	A
Pulse Source to Drain Current (Note 3)	I_{SDM}		-	-	12	A
Source to Drain Diode Voltage (Note 2)	V_{SD}	$T_J = 25^oC$, $I_{SD} = 3.1A$, $V_{GS} = 0V$, (Figure 13)	-	-	1.6	V
Reverse Recovery Time	t_{rr}	$T_J = 25^oC$, $I_{SD} = 3.1A$, $dI_{SD}/dt = 100A/\mu s$	120	270	600	ns
Reverse Recovery Charge	Q_{RR}	$T_J = 25^oC$, $I_{SD} = 3.1A$, $dI_{SD}/dt = 100A/\mu s$	0.64	1.4	3.0	μC

NOTES:

2. Pulse test: pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
3. Repetitive rating: pulse width limited by maximum junction temperature. See Transient Thermal Impedance curve (Figure 3).
4. $V_{DD} = 50V$, starting $T_J = 25^oC$, $L = 3.1mH$, $R_{GS} = 25\Omega$, peak $I_{AS} = 3.1A$.

Typical Performance Curves Unless Otherwise Specified



FIGURE 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE



FIGURE 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE



FIGURE 3. MAXIMUM TRANSIENT THERMAL IMPEDANCE

©2001 Fairchild Semiconductor Corporation

Typical Performance Curves Unless Otherwise Specified (Continued)



FIGURE 4. FORWARD BIAS SAFE OPERATING AREA



FIGURE 5. OUTPUT CHARACTERISTICS



FIGURE 6. SATURATION CHARACTERISTICS



FIGURE 7. TRANSFER CHARACTERISTICS



FIGURE 8. DRAIN TO SOURCE ON RESISTANCE vs GATE VOLTAGE AND DRAIN CURRENT



FIGURE 9. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE

©2001 Fairchild Semiconductor Corporation

Typical Performance Curves Unless Otherwise Specified **(Continued)**



FIGURE 10. NORMALIZED DRAIN TO SOURCE BREAKDOWN VOLTAGE vs JUNCTION TEMPERATURE



FIGURE 11. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE



FIGURE 12. TRANSCONDUCTANCE vs DRAIN CURRENT



FIGURE 13. SOURCE TO DRAIN DIODE VOLTAGE



FIGURE 14. GATE TO SOURCE VOLTAGE vs GATE CHARGE

©2001 Fairchild Semiconductor Corporation

Test Circuits and Waveforms



FIGURE 15. UNCLAMPED ENERGY TEST CIRCUIT



FIGURE 16. UNCLAMPED ENERGY WAVEFORMS



FIGURE 17. SWITCHING TIME TEST CIRCUIT



FIGURE 18. RESISTIVE SWITCHING WAVEFORMS



FIGURE 19. GATE CHARGE TEST CIRCUIT



FIGURE 20. GATE CHARGE WAVEFORMS

©2001 Fairchild Semiconductor Corporation

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FAST ®	PACMAN™	SuperSOT™-3
Bottomless™	FASTr™	POP™	SuperSOT™-6
CoolFET™	GlobalOptoisolator™	PowerTrench ®	SuperSOT™-8
CROSSVOLT™	GTO™	QFET™	SyncFET™
DenseTrench™	HiSeC™	QS™	TinyLogic™
DOME™	ISOPLANAR™	QT Optoelectronics™	UHC™
EcoSPARK™	LittleFET™	Quiet Series™	UltraFET™
E^2CMOS^{TM}	MicroFET™	SILENT SWITCHER ®	VCX™
EnSigna™	MICROWIRE™	SMART START™	
FACT™	OPTOLOGIC™	Star* Power™	
FACT Quiet Series™	OPTOPLANAR™	Stealth™	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.