TAVAKOL ELECTRONIC
توکل الکترونیک
مرجع تخصصی تأمین قطعات الکترونیکی اورجینال

این دیتاشیت توسط توکل الکترونیک تهیه و ارائه شده است.

جهت مشاهده قیمت، موجودی و ثبت سفارش این قطعه به وب‌سایت توکل الکترونیک مراجعه فرمایید.

مشاهده قیمت و خرید
برای خرید و مشاهده سایر محصولات کلیک کنید

NIKO-SEM

N-Channel Enhancement Mode Field Effect Transistor

P1308ATG
TO-220
Halogen-Free & Lead-Free

RoHS Compliant

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
75	13mΩ	62A





1. GATE
2. DRAIN
3. SOURCE

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_C = 25 °C	I_D	62	A
	T_C = 100 °C		39	
Pulsed Drain Current[1]		I_{DM}	200	
Avalanche Current		I_{AS}	53	
Avalanche Energy	L = 0.1mH	E_{AS}	140	mJ
Power Dissipation	T_C = 25 °C	P_D	96	W
	T_C = 100 °C		38	
Operating Junction & Storage Temperature Range		T_j, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		1.3	°C / W
Junction-to-Ambient	$R_{\theta JA}$		62.5	

[1]Pulse width limited by maximum junction temperature.

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS MIN	LIMITS TYP	LIMITS MAX	UNIT
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = 250μA	75			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250μA	1.5	2.3	4.0	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0V, V_{GS} = ±20V			±250	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 60V, V_{GS} = 0V			1	μA
		V_{DS} = 60V, V_{GS} = 0V, T_J = 125 °C			10	
On-State Drain Current[1]	$I_{D(ON)}$	V_{DS} = 10V, V_{GS} = 10V	200			A
Drain-Source On-State Resistance[1]	$R_{DS(ON)}$	V_{GS} = 10V, I_D = 40A		9.5	13	mΩ
Forward Transconductance[1]	g_{fs}	V_{DS} = 10V, I_D = 40A		33		S

DYNAMIC						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = 25V, f = 1MHz		3370		pF
Output Capacitance	C_{oss}			279		
Reverse Transfer Capacitance	C_{rss}			276		
Total Gate Charge[2]	Q_g	V_{DS} =40V, V_{GS} = 10V, I_D = 40A		79		nC
Gate-Source Charge[2]	Q_{gs}			17.2		
Gate-Drain Charge[2]	Q_{gd}			33		
Turn-On Delay Time[2]	$t_{d(on)}$	V_{DD} = 40V, $I_D \cong$ 40A, V_{GS} = 10V, R_{GS} = 25Ω		43		nS
Rise Time[2]	t_r			212		
Turn-Off Delay Time[2]	$t_{d(off)}$			293		
Fall Time[2]	t_f			147		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_J = 25 °C)						
Continuous Current	I_S				62	A
Forward Voltage[1]	V_{SD}	I_F = 40A, V_{GS} = 0V			1.4	V
Reverse Recovery Time	t_{rr}	I_F = 40A, dI_F/dt = 100A / μS		45		nS
Reverse Recovery Charge	Q_{rr}			70		nC

[1]Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.
[2]Independent of operating temperature.

Output Characteristics



Transfer Characteristics



On-Resistance VS Temperature



Capacitance Characteristic



Gate charge Characteristics



Source-Drain Diode Forward Voltage



Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve